

Provided by Xpert Survey Equipment
[Click Trimble VX DR Plus for Product Info and Updated Pricing](#)

KEY FEATURES

Surveying, imaging and 3D scanning in one powerful solution

Increase your agility to adapt to any situation

Create enhanced 2D and 3D deliverables for rich information management



Capture and combine scanning, imaging and surveying deliverables with the singular solution designed for surveyors. Integrating the technologies of advanced optical surveying, metric imaging and 3D scanning, the Trimble[®] VX[™] Spatial Station is the only surveying instrument that does it all and does it with ease.

CAPTURE THE SHAPE OF THE REAL WORLD – EVERY DAY

Expectations from surveying customers are evolving. To improve the efficiency of capturing advanced Spatial Imaging deliverables, Trimble provides an integrated solution for bringing these technologies together within the traditional workflows surveyors already use. So you have the flexibility to perform feature-rich scans every day, without the complexity of setting up a separate scanning system or switching to specialized field software.

With the Trimble VX Spatial Station, you can efficiently capture the information you need to create digital terrain models (DTMs), volume calculations, and perform topographic measurements faster than with traditional surveying methods.

HARNESS THE POWER OF TRIMBLE REALWORKS SOFTWARE

Advanced 3D models and image-rendered 3D surfaces are within your reach with the rich data delivered by Trimble Spatial Imaging sensors. With the ability to capture metric images with the Trimble VX in the field, you are also able to make additional measurements and attribute the data back in the office. It's all accessible to surveyors with the Trimble VX and Trimble RealWorks[®] software. Your clients will immediately see the detail of your work via 3D walkthroughs of the job site using your survey data, images, and scanned information all from the Trimble VX.

VIDEO-ASSISTED CONTROL

Trimble VISION[™] gives you the power to see everything the instrument sees. Direct your work with live video images on the controller. Now you are free to capture measurements to prism or reflectorless surface with a point and click.

COMBINE GNSS AND OPTICAL DATA

Take your productivity even further by adopting Trimble Integrated Surveying[™] workflows – simply add your GNSS receiver to your robotic rod and powerful Trimble field software will seamlessly take care of the rest. This allows you to collect GNSS and optical data while simultaneously scanning a surface or site. With the built-in imaging and 3D scanning capabilities, you can capture the shape of objects of interest, such as a nearby building or power lines while you perform your traditional survey work.

With the long range capabilities of the Trimble DR Plus EDM, you measure further with fewer instrument set-ups and enhance your scanning performance.

PERFORMANCE

Scanning (not enabled on all models)

Range ^{1, 2}	from 1 m up to 250 m (3.28 ft–820 ft)
Speed ⁶	up to 15 points/sec, typical 5 points/sec
Minimum point spacing	10 mm (0.032 ft)
Standard deviation	3 mm @ ≤150 m (0.0098 ft @ ≤492 ft)
Single 3D point accuracy	10 mm @ ≤150 m (0.032 ft @ ≤492 ft)
Angle accuracy	1" (0.3 mgon)
Sensor type	Absolute encoder with diametrical reading
Automatic level compensator	
Type	Centered dual-axis
Accuracy	0.5" (0.15 mgon)
Range	±5.4' (±100 mgon)

Other distance measurement

Accuracy (RMSE)

Prism mode	
Standard	.2 mm + 2 ppm (0.0065 ft + 2 ppm)
Standard deviation according to ISO17123-4	.1 mm + 2 ppm (0.003 ft + 2 ppm)
Tracking	.4 mm + 2 ppm (0.013 ft + 2 ppm)
DR mode	
Standard	.2 mm + 2 ppm (0.0065 ft + 2 ppm)
Tracking	.4 mm + 2 ppm (0.013 ft + 2 ppm)

Measuring time

Prism mode	
Standard	.1–2 sec
Tracking	.0–.4 sec
DR mode	
Standard	1–5 sec
Tracking	.0–.4 sec

Range

Prism mode (under standard clear conditions ^{4,5})	
1 prism	2,500 m (8,202 ft)
1 prism Long Range mode	5,500 m (18,044 ft) (max. range)
Shortest possible range	0.2 m (0.65 ft)
DR mode	

	Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
White card (90% reflective) ²	1,300 m (4,265 ft)	1,300 m (4,265 ft)	1,200 m (3,937 ft)
Gray card (18% reflective) ²	600 m (1,969 ft)	600 m (1,969 ft)	550 m (1,804 ft)

Shortest possible range	.1 m (3.28 ft)
DR Ranges (typically)	
Concrete	600–800 m (1,968–2,624 ft)
Wood construction	400–800 m (1,312–2,624 ft)
Metal construction	400–500 m (1,312–1,640 ft)
Light rock	400–600 m (1,312–1,968 ft)
Dark rock	300–400 m (984–1,312 ft)
Reflective foil 20 mm	1,000 m (3,280 ft)
Extended Range Mode	
White Card (90% reflective) ²	2,000–2,200 m
Gray Card (18% reflective) ²	900–1,000 m
Accuracy	10 mm + 2 ppm (0.033 ft + 2 ppm)

ROBOTIC OPERATION

Range⁵

Passive prisms	500–700 m (1,640–2,297 ft)
Trimble MultiTrack Target	.800 m (2,625 ft)
Autolock pointing precision at 200 m (656 ft) (Standard deviation) ⁵	
Passive prisms	<2 mm (0.007 ft)
Trimble MultiTrack Target	<2 mm (0.007 ft)
Shortest search distance	0.2 m (0.65 ft)
Type of radio internal/external	2.4 GHz frequency-hopping, spread-spectrum radios
Search time (typical) ⁶	2–10 sec

SySTEM SPECIFICATIONS

Leveling

Circular level in tribrach	8/2 mm (8/0 .007 ft)
Electronic 2-axis level in the LC-display with a resolution of	.0 .3" (0 .1 mgon)

Servo system MagDrive servo technology, integrated servo/angle sensor electromagnetic direct drive

Rotation speed 115 degrees/sec (128 gon/sec)

Rotation time Face 1 to Face 2 .2 .6 sec

Positioning speed 180 degrees (200 gon) .2 .6 sec

Clamps and slow motions

Centering

Centering system	Trimble 3-pin
Optical plummet	Built-in optical plummet
Magnification/shortest focusing distance	2 .3x/0 .5 m

Telescope

Magnification	.30x
Aperture	.40 mm (1 .57 in)
Field of view at 100 m (328 ft)	.2 .6 m at 100 m (8 .5 ft at 328 ft)
Shortest focusing distance	1 .5 m (4 .92 ft) to infinity
Illuminated crosshair	Variable (10 steps)
Autofocus	Standard

Camera

Chip	Color Digital Image Sensor
Resolution	2048 x 1536 pixels
Focal length	.23 mm (0 .07 ft)
Depth of field	.3 m to infinity (9 .84 ft to infinity)
Field of view	16 .5° x 12 .3° (18 .3 gon x 13 .7 gon)
Digital zoom	4-step (1x, 2x, 4x, 8x)
Exposure	Automatic
Brightness	User-definable
Contrast	User-definable
Image storage	Up to 2048 x 1536 pixels
File format	JPEG
Compression ratio	User-definable
Video streaming ⁷	5 frames/sec

Operating temperature -20 °C to +50 °C (-4 °F to +122 °F)

Dust and water proofing IP55

Power supply

Internal battery	Rechargeable Li-Ion battery 11 .1 V, 4 .4 Ah
Operating time ⁸	
One internal battery	Approx . 5 hours
Three internal batteries in multi-battery adapter	Approx . 15 hours
Robotic holder with one internal battery	Approx . 12 hours

Weight

Instrument	5 .25 kg (11 .57 lb)
Trimble CU controller	0 .4 kg (0 .88 lb)
Tribrach	0 .7 kg (1 .54 lb)
Internal battery	0 .35 kg (0 .77 lb)

Trunnion axis height .196 mm (7 .71 in)

Communication USB, Serial, Bluetooth

Security Dual-layer password protection

EDM SPECIFICATIONS

Light source Pulsed Laser diode 905 nm; Laser class 1

Laser pointer coaxial Laser class 2

Beam divergence Prism mode

Horizontal	.4 cm/100 m (0 .13 ft/328 ft)
Vertical	.8 cm/100 m (0 .13 ft/328 ft)

Beam divergence DR mode

Horizontal	.4 cm/100 m (0 .13 ft/328 ft)
Vertical	.8 cm/100 m (0 .13 ft/328 ft)

Atmospheric correction -130 ppm to 160 ppm continuously



THE HINZE DAM

“When you consider that the Trimble VX reduces our surveying time and allows quarrying to carry on uninterrupted, you really couldn't ask for a better survey technique for this job.”

— Todd Foster, Hinze Dam Alliance

- 1 Target color, atmospheric conditions, and scanning angles will impact range.
- 2 Kodak Gray Card, Catalog number E1527795.
- 3 Target shape, texture, and color; grid size; and distance and angle to target; will impact speed.
- 4 Standard clear; No haze. Overcast or moderate sunlight with very light heat shimmer.
- 5 Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.
- 6 Dependent on selected size of search window.
- 7 0.5 frames per second with remote operation.
- 8 The capacity in -20 °C (-5 °F) is 75% of the capacity at +20 °C (68 °F).
- 9 Bluetooth type approvals are country specific. Contact your local Trimble Authorized Distribution Partner for more information.



© 2007–2010, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited registered in the United States and in other countries. Integrated Surveying, VISION, and VX are trademarks of Trimble Navigation Limited. RealWorks is a registered trademark of Mensi SA. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022543-261F (01/10)



TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

NORTH AMERICA
 Trimble Engineering &
 Construction Group
 5475 Kellenburger Road
 Dayton, Ohio 45424-1099 • USA
 800-538-7800 (Toll Free)
 +1-937-245-5154 Phone
 +1-937-233-9441 Fax

EUROPE
 Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim • GERMANY
 +49-6142-2100-0 Phone
 +49-6142-2100-550 Fax

ASIA-PACIFIC
 Trimble Navigation
 Singapore Pty Limited
 80 Marine Parade Road
 #22-06, Parkway Parade
 Singapore 449269 • SINGAPORE
 +65-6348-2212 Phone
 +65-6348-2232 Fax



www.trimble.com